IN THE CLAIMS

1.   (currently amended) An in-circuit emulation system, comprising:

a microcontroller;

a virtual microcontroller coupled to and executing instructions in lock-step with the microcontroller, and wherein the microcontroller sends I/O read data to the virtual microcontroller;

the virtual microcontroller having means for detecting a~~sequence of instructions comprising~~ an I/O read instruction followed by a conditional jump instruction, and for computing a conditional jump address prior to receipt of I/O read data from the microcontroller; and

the virtual microcontroller further having means for determining after receipt of the I/O read data from the microcontroller whether to proceed with instruction execution at a next consecutive address or at the conditional jump address.

2.   (original) The apparatus according to claim 1, wherein the conditional jump address is computed while the I/O read data are sent from the microcontroller to the virtual microcontroller.

3.   (original) The apparatus according to claim 1, wherein the microcontroller sets a zero flag if an I/O read test condition is met.

4.   (original) The apparatus according to claim 3, wherein the jump condition is met if the zero flag is set.

5.   (original)   The apparatus according to claim 1, wherein the virtual microcontroller is implemented in a Field Programmable Gate Array.

6.   (currently amended)   In an in-circuit emulation system having a microcontroller coupled to and operating in lock-step with a virtual microcontroller, a method of handling conditional jumps in the virtual microcontroller, comprising:

    detecting a~~ sequence of instructions comprising~~ an I/O read instruction followed by a conditional jump instruction;

    computing a conditional jump address prior to receipt of I/O read data from the microcontroller; and

    determining after receipt of the I/O read data from the microcontroller whether to proceed with instruction execution at a next consecutive address or at the conditional jump address.

7.   (original) The method according to claim 6, further comprising executing a next consecutive instruction in the event a conditional jump condition is not met.

8.   (original) The method according to claim 6, further comprising executing an instruction at the conditional jump address in the event the conditional jump condition is met.

9.   (original) The method according to claim 6, wherein the conditional jump address is computed while the I/O read data are sent from the microcontroller to the virtual microcontroller.

10.   (original) The method according to claim 6, wherein the microcontroller sets a zero flag if an I/O read test condition is met.

11.   (original) The method according to claim 10, wherein the jump condition is met if the zero flag is set.

12.   (original) The method according to claim 6, wherein the virtual microcontroller is implemented in a Field Programmable Gate Array.

13.   (original) The method according to claim 6, stored as instructions stored in an electronic storage medium for execution as program steps on a programmed processor forming a part of the virtual microcontroller.

14.   (currently amended) In an in-circuit emulation system having a device under test coupled to and operating in lock-step with a virtual processor, a method of handling conditional jumps in the virtual processor, comprising:

detecting a sequence of instructions comprising an I/O read instruction followed by a conditional jump instruction;

computing a conditional jump address prior to receipt of I/O read data from the virtual processor; and

determining after receipt of the I/O read data from the device under test whether to proceed with instruction execution at a next consecutive address or at the conditional jump address.

15.   (original) The method according to claim 14, further comprising executing a next consecutive instruction in the event a conditional jump condition is not met.

16.   (original) The method according to claim 14, further comprising executing an instruction at the conditional jump address in the event the conditional jump condition is met.

17.   (original) The method according to claim 14, wherein the conditional jump address is computed while the I/O read data are sent from the device under test to the virtual processor.

18.   (original) The method according to claim 14, wherein the device under test sets a zero flag if an I/O read test condition is met.

19.   (original) The method according to claim 18, wherein the jump condition is met if the zero flag is set.

20.   (original) The method according to claim 14, wherein the virtual processor is implemented in a Field Programmable Gate Array.